



COARSE BLEND LCM

PRODUCT DESCRIPTION

COMBAT combines high-stream granular particles with sized bridging materials. This product is formulated to provide operators with a high-performance sealant designed for use in highly fractured and vugular formations.

COMBAT can be used in conjunction with F.I.T.[™] and FIRST STRIKE[™] in a lost circulation pill, in concentrations of 5 – 25 ppb of each. These pills may be used in sweep fashion or spotted downhole for a period of 2 – 4 hours to affect a lasting seal. Applying a soft squeeze with a pill in place will further advance sealing effectiveness.

PRIMARY APPLICATIONS

- Sealing high permeability sands where substantial seepage losses occur.
- Stopping major loss of mud and workover fluids in fractured formations.
- Temporary sealing of holes in casing during drilling and workover operations.



PHYSICAL PROPERTIES

- Appearance: Dark grey mixture of flakes and granules
- Bulk Density: 40 – 65 lb/ft³

PACKAGING

- COMBAT is provided in 25 pound bags, palletized and shrink-wrapped.
- There are 100 sacks per pallet (100sx/pal).

Fort Lupton, Colorado | Lafayette, Louisiana | Elk City, Oklahoma |
Williston, North Dakota | Conroe, Texas | Corpus Christi, Texas |
Midland, Texas | Casper, Wyoming

DRILLCHEM
DRILLING • COMPLETION • PRODUCTION
281.713.8941 | drillchem.com